

# Quick Set Up Check List

## Spa location has been identified

- Solid, flat and level foundation
- Clear path for delivery - no obstructions for height, width, bushes, trees, walkways

## Locate and read the owner's manual

- Owner's manual is located in the bag inside the main spa body

## Electrical requirements met

- Dedicated electrical with GFCI protection (see owner's manual)
- 120v spas are connected to a dedicated electrical outlet

## Inspect the equipment (open equipment compartment)

- Make sure gate valves are open
- Drain cap is on and in closed position
- All visible plumbing unions are snug
- Replace equipment door

## Filling your spa with water

- Remove the new filter cartridge and unwrap
- Soak your filter in water for approximately 30 minutes
- Fill spa with hose through the filter canister area of your spa
- Fill spa with water until about 6" from the top of the spa

## Turning on the spa

- Turn on power at the GFCI Breaker
- Or plug in your spa to a dedicated electrical outlet for 120v spas
- Spa will go into self-diagnostic mode and begin priming
- To self-prime see owner's manual
- Replace the filter cartridge in your spa

## Adjust water chemistry

- Adjust chemistry as described in your owner's manual
- Close the spa cover; when the spa is primed it will begin heating

## Register your spa for warranty purposes

- Spa can be registered online at <https://calspas.com/register-your-spa.php>